



ZÜMRÜT INTERNATIONAL KİMYA SAN. VE TİC.LTD

Technical Datasheet of Blown Bitumen 105/15

CHARACTERISTIC	Test method	Unit	Specification
Specific gravity @25/25 C	ASTM D70	(Kg/m ³)	1.05 approx.
Penetration @ 25°C	ASTM D5	mm/10	20-Oct
Softening point °C	ASTM D36	°C	100/110
Loss on heating(wt) %	ASTM D6	Wt. %	0.2 max
Flashpoint c	ASTM D92	°C	250 min
Solubility is CS2(wt) %	ASTM D4	Wt. %	99.5 max
Spot test	A.A.S.H.O.T102	—	Negative

The unique advantage of blown asphalt 105/15

Blown asphalt 105/15, also known as oxidized bitumen, has unique advantages that make it highly sought after in various industrial applications. Here are some of its standout properties:

1. **Enhanced Durability and Stability**
2. **Resistance to Deformation**
3. **Superior Waterproofing Qualities**
4. **Chemical and Weather Resistance**
5. **Wide Application Range**

Packing:

Zumrut Co is the manufacturer of Blown Bitumen 105/15 in various packing, including bitumen 105/15 is available in 20 & 50 Kg Kraft Paper Bags / Poly Amide Bags, 25 Kg Carton box & 150, 180, 200kg Steel Drums. In addition, oxidized bitumen packing also palletize, 40 bags can stack on the pallet. 20 pallet can load to the 20ft container



Karşıyaka mahallesi, 749 sokak ,No 30 ,
Gölbaşı/Ankara/Türkiye



www.zumrut-int.com



+90 555 160 57 39
+90 312 544 45 81



Info@zumrut-int.com