



ZÜMRÜT INTERNATIONAL KİMYA SAN. VE TİC.LTD

## Technical Data Sheet of Bitumen Rubber Mastic Sealant

<i>PROPERTIES</i>	<i>VALUES</i>	<i>TEST STANDARDS</i>
<i>Color</i>	<i>Black</i>	-
<i>Form</i>	<i>Paste</i>	-
<i>Solid content, [%]</i>	<i>&gt;80</i>	<i>ASTM D 2939</i>
<i>Slump</i>	<i>Nil</i>	-
<i>Density, [g/cc]</i>	<i>1.1 ± 0.05</i>	<i>ASTM D 1475</i>
<i>Initial set @ standard condition, [hours]</i>	<i>24 -48</i>	
<i>Full cure @ standard condition, [days]</i>	<i>14-21 days</i>	
<i>Chemical resistance</i>	<i>Sea water, chlorides and sulphate ions.</i>	<i>ASTM D 543</i>

### **Key Applications of Bitumen Rubber Mastic Sealant**

- *Joint & Crack Sealing*
- *Roof & Waterproofing Repairs*
- *Underground Structures & Foundations*
- *Industrial & Marine Applications*
- *Concrete & Masonry Joints*
- *Metal & Pipe Protection*
- *General Waterproofing & Adhesive Uses*



Karşıyaka mahallesi, 749 sokak ,No 30 ,  
Gölbaşı/Ankara/Türkiye



[www.zumrut-int.com](http://www.zumrut-int.com)



+90 555 160 57 39  
+90 312 544 45 81



[Info@zumrut-int.com](mailto:Info@zumrut-int.com)