



ZÜMRÜT INTERNATIONAL KİMYA SAN. VE TİC.LTD

Specification of Zumrut Kimya RC base oil SN150

SPECIFICATION	MIN	MAX	METHOD
Viscosity @100°C	6	7.5	ASTM D-445
Viscosity @40°C	35	55	ASTM D-445
Viscosity Index	100	110	ASTM D-2270
Flash Point °C	180	190	ASTM D-92
Pour point	0	0	ASTM D-97
Total Acid Number mgKOH/g	0	0.03	ASTM D-664
Color	2	2.5	ASTM D-1500
Density	0.868	0.874	ASTM D-1298

Key Characteristics of Recycled Base Oil

- **High Purity:**
*Undesirable contaminants, such as water, dirt, and heavy metals, are removed during the refining process.
Restores oil to a clean and reusable state.*
- **Eco-Friendly:**
*Promotes sustainability by reducing waste and minimizing the need for virgin oil extraction.
Helps in conserving natural resources and reducing environmental pollution.*
- **Versatile Applications:**
*Suitable for use in lubricants, greases, hydraulic oils, and other industrial fluids.
Provides comparable performance to virgin base oils.*



Karşıyaka mahallesi, 749 sokak, No 30,
Gölbaşı/Ankara/Türkiye



www.zumrut-int.com



+90 555 160 57 39
+90 312 544 45 81



Info@zumrut-int.com