



ZÜMRÜT INTERNATIONAL KİMYA SAN. VE TİC.LTD

Data Sheet of Drilling Fluid loss control (FCL)

TEST	RESULT	TEST METHOD
ASH CONTENT,WT%	5	ASTM-D3174
MOISTURE CONTENT,WT%	1	ASTM-D3173
VOLATILE MATTER,WT%	63	ASTM-D3175
SOLUBILITY IS CS ₂ ,WT	81	ASTM-D4
SPECIFIC GRAVITY @25C	1.11	ASTM-3289
NORMAL NEPTHAN INSOLUBLES,WT%	79	ASTM-3279
COLOR IS MASS	BLACK	_____
COLOR IN STREAK OR POWDER	BLACK	_____
SOFTENING POINT,C	210	ASTM-D36
PENETRATION @25C	0	ASTM-D5

Benefits of Using Gilsonite in Drilling Fluids

- ***Effective Fluid Loss Control***
- ***Improved Lubrication***
- ***Environmentally Friendly***
- ***Cost-Effectiveness***
- ***Resistance to Acid and Alkali Conditions***



Karşıyaka mahallesi,749 sokak ,No 30 ,
Gölbaşı/Ankara/Türkiye



www.zumrut-int.com



+90 555 160 57 39
+90 312 544 45 81



Info@zumrut-int.com

