



ZÜMRÜT INTERNATIONAL KİMYA SAN. VE TİC.LTD

Specification of Natural rubber

Parameter	Unit	SMR	SMR	SMR	SMR	SMR	SMR	SMR	SMR	SMR
		CV50	CV60	L	5	GP	10	10CV	20	20CV
Dirt (max)	%wt	0.02	0.02	0.02	0.05	0.08	0.08	0.08	0.16	0.16
Ash (max)	%wt	0.5	0.5	0.5	0.6	0.75	0.75	0.75	1	1
Nitrogen (max)	%wt	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
Volatile Matter (max)	%wt	0.8	0.8	0.5	0.8	0.8	0.8	0.8	0.8	0.8
Po (min)		NA	NA	35	30	NA	30	NA	30	NA
PRI Index (min)		60	60	60	60	50	50	50	40	40
Lovibond Color: individual value (max)		NA	NA	6	NA	NA	NA	NA	NA	NA
Lovibond Color: range (max)		NA	NA	2	NA	NA	NA	NA	NA	NA
Mooney Viscosity (ML, 1+4, 100°C)		50 +/- 5	60 +/- 5	NA	NA	65 -1.4	NA	60 -1.4	NA	65 +/-5



Karşıyaka mahallesi,749 sokak ,No 30 ,
Gölbaşı/Ankara/Türkiye



www.zumrut-int.com



+90 555 160 57 39
+90 312 544 45 81



Info@zumrut-int.com